

6 dBd HD omni antenna 380 - 430 MHz, Low PIM

DESCRIPTION

- The 4220 Series omni antenna is designed for demanding applications where a durable and high performance colinear is required.
- The centre fed dipole design and feed network gives a stable radiation pattern across a wide bandwidth, and allows tilted beam designs to be effectively employed without large pattern distortions.
- High quality materials and manufacturing techniques are employed to ensure that the antenna has excellent intermodulation performance & wide bandwidth characteristics for multi-channel trunked radio communication systems.
- The antenna has been designed to withstand lightning strike.
- Former Skymasts brand product.




SPECIFICATIONS

Electrical	
Model	4220.06-405-Txx
Frequency	380 - 430 MHz
Max. Input Power	300 W
Omni Deviation	< ± 1 dB
Polarisation	Vertical
Peak Instantaneous Power (PIP)	25 kW
3 dB Beamwidth, E-Plane	16° ±1°
3 dB Beamwidth, H-Plane	Omnidirectional
Impedance	50 Ω
Gain	6 dBd (8.2 dBi)
VSWR	< 1.5:1
Passive Intermodulation	-153 dBc (3rd Order, 2 x Tx @ 43 dBm)
Lightning Protection	Lightning current handling capability : 200 kA According to EN 62305-1 (Test pulse 10/350 µs)
Antistatic Protection	All metal parts DC-grounded (Connector shows a DC-short)
Mechanical	
Connection(s)	7/16 DIN(f)
Materials	Antenna Base : Aluminium Shroud : GRP tube 53 mm dia.
Mounting Section	Al. tube 63.5 mm dia. x 350 mm long
Dimensions	2900 (l) x 53 (dia.) mm / 114.17 x 2.09 (dia.) in.
Wind Load	230 N (160 km/h)
Weight	Approx. 8.1 kg / 17.86 lb.
Mounting Bracket	2141.01.00.00 (up to 120 mm dia.) (Ordered Separately) ETC-250 (50 to 76 mm dia.) (Ordered Separately)
Environmental	
Operating Temperature Range	-40 °C to +70 °C
Survival Wind Speed	300 km/h
Ingress Protection	IP56

ORDERING


Model	Product No.	Description	Frequency
6 dBd HD omni antenna, low PIM	4220.06-405-T0	0° Electrical Tilt	380 - 430 MHz
6 dBd HD omni antenna, low PIM	4220.06-405-T4	4° Electrical Tilt	380 - 430 MHz
6 dBd HD omni antenna, low PIM	4220.06-405-T5	5° Electrical Tilt	380 - 430 MHz
6 dBd HD omni antenna, low PIM	4220.06-405-T6	6° Electrical Tilt	380 - 430 MHz
6 dBd HD omni antenna, low PIM	4220.06-405-T8	8° Electrical Tilt	380 - 430 MHz
6 dBd HD omni antenna, low PIM	4220.06-405-T10	10° Electrical Tilt	380 - 430 MHz
6 dBd HD omni antenna, low PIM	4220.06-405-T12	12° Electrical Tilt	380 - 430 MHz
Accessories			
Galvanised steel parallel bracket	2141.01.00.00	38 - 120 mm (PAIR)	
Extruded Parallel Tube Clamp	ETC-250	50 - 76 mm	

RADIATION PATTERN



E-Plane | 405 MHz

RADIATION PATTERN



H-Plane | 405 MHz

