

Centre fed dipole 380-430 MHz

DESCRIPTION

A UHF Center Fed Dipole antenna for PMR/Trunked Radio and UHF Aircraft Band applications. Multiple dipoles can be mounted on a tower and connected with a phasing harness to form a high gain, stacked array. Produced to the highest quality standards, these robust antenna designs will ensure reliable operation in harsh environmental conditions. • Former Jaybeam brand product.

SPECIFICATIONS

Electrical		
Frequency	380 - 430 MHz	
Max. Input Power	150 W	
Polarisation	Linear (Vertical or Horizontal)	
3 dB Beamwidth, E- Plane	80 °	
3 dB Beamwidth, H- Plane	Omni - will depend on mounting distance from mast.	
Impedance	50 Ω	
Gain	0 dBd (omni - will depend on mounting distance from mast)	
VSWR	< 1.5:1	
Antistatic Protection	All metal parts DC-grounded (Connector shows a DC-short)	
In iBwave	Yes	

Mechanical	
Connection(s)	N(f) on 3m RG213/U cable
Materials	Boom, 32 mm dia. aluminium elements, 12.7 mm dia. aluminium balun, Fully moulded enclosure
Dimensions	1370 x 330 x 100mm (L x H x D)
Wind Load	69 N (160km/h)
Weight	1.8 kg / 3.97 lb
Mounting Bracket	3202078/68 + 3201079/00 (Ordered Separately)
Alternate Mounting Bracket	0900912/00, 0302032/68, or 0300064/00 + U-Bolts to match mounting pipe diameter (Ordered Separately)

ORDERING

Туре	Product No.	Frequency
Centre fed dipole 380-430 MHz	7051400	380 - 430 MHz
Galvanised steel crossover bracket 32/50mm	0900912/00	
Pressed steel cross clamp 2" x 1-1/4" (JBL73)	0302032/68	
Cast aluminium cross clamp, circular	0300064/00	
M8 x 50mm (2") U-Bolts (1 Pair)	4884036/00	
M8 x 75mm (3") U-Bolts (1 Pair)	4884076/00	
Fixed norstel / coupler clamp (cross clamp)	3202078/68	
Increasing sleeve	3201079/00	



DIAGRAM

RADIATION PATTERNS



RADIATION PATTERNS

