

CMAX-DMF4-43-WI53



Low PIM Directional 4X4 MIMO In-Building Antenna, 698–960 MHz, 1695–2700 MHz and 3300–4200MHz

Product Classification

Product Type In-building antenna

General Specifications

Application Indoor/Outdoor
Antenna Type Directional
Antenna Array Characteristic MIMO 4x4
Polarization $\pm 45^\circ$
Color White (RAL 9016)
Number of Ports 4
Pigtail Cable 670-141SXE, plenum rated
Radome Material ASA+PC, UV stabilized
RF Connector Interface 4.3-10 Female

Dimensions

Width 332 mm | 13.071 in
Depth 100 mm | 3.937 in
Length 458 mm | 18.032 in
Pigtail Length 450 mm | 17.717 in

Electrical Specifications

Electrical Note Values typical, unless otherwise stated
Impedance 50 ohm
Operating Frequency Band 1695 – 2700 MHz | 3300 – 4200 MHz | 698 – 960 MHz

CMAX-DMF4-43-WI53

Electrical Specifications

Frequency Band, MHz	698–800	800–960	1695–2200	2200–2700	3300–4200
Gain, dBi	7	7.5	7.5	7.8	7.7
Beamwidth, Horizontal, degrees	90	80	71	67	68
Beamwidth, Vertical, degrees	70	69	72	73	69
Front-to-Back Ratio, Copolarization 180° ± 30°, dB	15	15	15	15	15
Isolation, Cross Polarization, dB	18	20	25	25	25
VSWR Return loss, dB	1.7 11.7	1.7 11.7	1.7 11.7	1.7 11.7	1.7 11.7
PIM, 3rd Order, 2 x 20 W, dBc	-153	-153	-153	-153	-153
Input Power per Port, maximum, watts	100	100	100	100	100

Environmental Specifications

Operating Temperature	-40 °C to +60 °C (-40 °F to +140 °F)
Relative Humidity	Up to 100%

Packaging and Weights

Width, packed	390 mm 15.354 in
Depth, packed	215 mm 8.465 in
Length, packed	665 mm 26.181 in
Included	Mounting bracket
Net Weight, with mounting kit	4.3 kg 9.48 lb
Packaging quantity	1
Weight, gross	6.2 kg 13.669 lb

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant

