

CMAX-OMF3-43-UWI53



Cell-Max™ Low PIM Omni MIMO In-building Antenna, 1695–2700, 3300–4200, 4900–6000 MHz

Product Classification

Product Type	In-building antenna
Product Brand	Cell-Max™

General Specifications

Antenna Type	Omni
Application	Indoor
Color	White
Mounting	Thru-hole ceiling mount (optional)
Number of Ports, all types	2
Pigtail Cable	670-141SXE, plenum rated
RF Connector Interface	4.3-10 Female

Dimensions

Height	108 mm 4.252 in
Pigtail Length	500 mm 19.685 in
Outer Diameter	176 mm 6.929 in

Electrical Specifications

Impedance	50 ohm
Operating Frequency Band	1695 – 2700 MHz 3300 – 4200 MHz 4900 – 6000 MHz
Polarization	Horizontal Vertical

Electrical Specifications

Frequency Band, MHz	1695–2700	3300–4200	4900–6000
Gain, dBi	3	4	4

CMAX-OMF3-43-UWI53

Beamwidth, Horizontal, degrees	360	360	360
Isolation, Cross Polarization, dB	23	28	28
VSWR Return loss, dB	1.8 10.9	1.7 11.7	1.7 11.7
PIM, 3rd Order, 2 x 20 W, dBc	-153	-153	
Input Power per Port, maximum, watts	50	50	50

Material Specifications

Radome Material	ABS
-----------------	-----

Environmental Specifications

Operating Temperature	-40 °C to +60 °C (-40 °F to +140 °F)
Relative Humidity	Up to 100%

Packaging and Weights

Width, packed	175 mm 6.89 in
Depth, packed	190 mm 7.48 in
Length, packed	175 mm 6.89 in
Weight, gross	0.6 kg 1.323 lb
Weight, net	0.5 kg 1.102 lb

Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system

