

MODEL	SPECIFICATIONS
303/323(white)	
ANTENNA TYPE	Heavy duty omni-directional MIMO 2 x LTE antenna for roof mounting on trucks, trailers etc. * LOW PROFILE DESIGN * CAR-WASH PROOF * NO GROUNDPLANE NEEDED
LTE Antenna: FREQUENCY IMPEDANCE POLARISATION GAIN (dBi) VSWR	2 x LTE MHz: 698-960 / 1710-2170 / 2300-2690 Nom. 50 Ω Vertical 2.5 $\pm$ 1 698-960 MHz 3.5 $\pm$ 1 1710-2170 MHz 2.0 $\pm$ 1 2300-2690 MHz < 2.2
MAX. POWER	20 Watt
COLOUR	Black / White
DIMENSIONS BUILD-IN DEPTH	$\varnothing$ 100 x 25 mm Approx. 16 mm
WEIGHT	Approx. 150 g
MOUNTING	Preferable on horizontal surface (Mounting hole $\varnothing$ 16 mm)
MATERIAL	Base: PA6 30% Radome: PA6 30% IP67 Classified (when mounted on vehicle); UV-resistance
TEMPERATURE	-40°C - +80°C

MOUNT TYPE	Bolt-on type with double self-adhesive tape for effective sealing
CABLE / CONNECTOR	2x LTE: ca. 0,30 m RG316 cable and Fakra (m) (RED)

