

# Dual Band Body Antenna

## DESCRIPTION

- Radio communication for the 160 MHz band and GPS-reception in one Antenna.
- > Highly flexible covert coax antenna with black sleeving.
- 🄰 ½ λ skirt dipole antenna.
- > Covert flexible body antenna, supporting free movement.
- > Highest quality materials in an elegant design.
- > Antenna available with SMA (male) or SMA (female) connector.

## ORDERING


| Туре              | Product No. |
|-------------------|-------------|
| BA 160/GPS        | 140000434   |
| BA 160/GPS-SMA(f) | 140000626   |
| BA 160/GPS White  | 140000698   |

#### SPECIFICATIONS

| Electrical       |  |
|------------------|--|
| Model            | BA 160/GPS                                     |
| Frequency        | 160 MHz : 150 - 170 MHz<br>GPS: 1575 MHz       |
| Antenna Type     | ½ λ antenna                                    |
| Max. Input Power | 25 W   |
| Polarisation     | Vertical                                       |
| Impedance        | 50 Ω   |
| Gain             | 160 MHz : 0 dBi (-5 dBi mounted on the body)   |
| VSWR             | 160 MHz : < 2.5 :1 when mounted in coat collar |
| Bandwidth        | 160 MHz : ≥ 20 MHz @ VSWR ≤ 2.5                |
|                  |  |

| Mechanical    |   |
|---------------|---|
| Connection(s) | SMA (male) or SMA (Female)                |
| Materials     | Coax cable with black sleeving            |
| Colour        | Black                                     |
| Height        | 860 mm / 33.86 in.                        |
| Weight        | Approx. 0.023 kg / 0.05 lb.               |
| Mounting      | Attached to clothing with two safety pins |

#### 3D GAIN PLOT \*



\* When antenna is mounted in front of chest.



MOUNTED ON THE BOBY



# TYPICAL VSWR CURVE

