

ATC200-LITE-USB-EU

Portable Controller for EU & UK



- Carried from site to site for RET antenna setup and optimization
- Supports up to 32 RET actuators operating in a mix of AISG modes
- LED display indicates the presence of input power, output power, and data communication
- Equipped with USB and serial connectors
- Power supply efficiency is Energy Star® Level IV rated.

General Specifications

AISG Output Connector	8-pin DIN Female
AISG Output Connector Quantity	1
Auxiliary Interface	USB
Color	Gray Yellow

Dimensions

Height	50.8 mm 2 in
Width	127 mm 5 in
Depth	76.2 mm 3 in

Electrical Specifications

Input Voltage	110/240 Vac
Output Current at Voltage, continuous	3.0 A @ 24 V
Output Current at Voltage, maximum	3.0 A @ 24 V
Output Voltage, typical	24 V
Electrical Safety Standard	CB CE IEC 60950-1
Interface Protocol Signal	Data dc
Power Supply	dc Jack
Protocol	AISG 1.1 AISG 2.0

Material Specifications

Material Type	Aluminum
----------------------	----------

Environmental Specifications

ATC200-LITE-USB-EU

Operating Temperature -40 °C to +55 °C (-40 °F to +131 °F)

Relative Humidity Up to 95%, non-condensing

Packaging and Weights

Included Adapter (Europe) | Adapter (United Kingdom) | Control unit | Power supply | Site configuration worksheet | USB cable

Weight, net 0.4 kg | 0.882 lb

Regulatory Compliance/Certifications

Agency	Classification
CE	Compliant with the relevant CE product directives
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant

