

# F4-HMHM-1M-D

---

D-CLASS Heliax 1/2" Superflexible SureFlex® Jumper with interface types 4.3-10 Male and 4.3-10 Male, 1 m



- WARNING: DO NOT MATE WITH 4.1-9.5 DIN

## Product Classification

|                       |                                |
|-----------------------|--------------------------------|
| <b>Product Type</b>   | SureFlex® D-CLASS, dynamic PIM |
| <b>Product Series</b> | RSJ4-50                        |

## General Specifications

|   |             |
|---|-------------|
| <b>Body Style, Connector A</b>            | Straight    |
| <b>Body Style, Connector B</b>            | Straight    |
| <b>Interface, Connector A</b>             | 4.3-10 Male |
| <b>Interface, Connector B</b>             | 4.3-10 Male |
| <b>Specification Sheet Revision Level</b> | B           |

## Dimensions

|                     |                |
|---------------------|----------------|
| <b>Length</b>       | 1 m   3.281 ft |
| <b>Nominal Size</b> | 1/2 in         |

## Electrical Specifications

|  |                                    |
|--|------------------------------------|
| <b>3rd Order IMD Dynamic</b>             | -119 dBm                           |
| <b>3rd Order IMD Dynamic Test Method</b> | Two +43 dBm carriers per IEC 62037 |
| <b>DTF, Connector A</b>                  | -34 dB                             |
| <b>DTF, Connector B</b>                  | -34 dB                             |

## Logo Image

# F4-HMHM-1M-D

---



## VSWR/Return Loss

| Frequency Band | VSWR | Return Loss (dB) |
|----------------|------|------------------|
| 698–960 MHz    | 1.07 | 30               |
| 1700–2200 MHz  | 1.07 | 30               |
| 2200–2700 MHz  | 1.09 | 28               |
| 3400–3800 MHz  | 1.23 | 20               |

## Jumper Assembly Sample Label

# F4-HMHM-1M-D



## Environmental Specifications

**Immersion Test Method** Meets IEC 60529:2001, IP68 in mated condition

## Regulatory Compliance/Certifications

| Agency        | Classification   |
|---------------|--|
| CHINA-ROHS    | Below maximum concentration value  |
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system   |
| REACH-SVHC    | Compliant as per SVHC revision on <a href="http://www.commscope.com/ProductCompliance">www.commscope.com/ProductCompliance</a> |
| ROHS          | Compliant  |

