Attenuator 2 W

DESCRIPTION

- This 2 W series includes 3 dB, 6 dB, 10 dB, 20 dB and 30 dB attenuators.
- This series of attenuators has very low SWR and attenuation flatness and is especially suitable for use with:
  - Coaxial Transmission Lines
  - Power Monitors
  - Watt Meters

ORDERING

Type	Product No.
PRO-ATT 3 dB-2-3-N	200002212
PRO-ATT 6 dB-2-3-N	200002213
PRO-ATT 10 dB-2-3-N	200002087
PRO-ATT 20 dB-2-3-N	200002214
PRO-ATT 30 dB-2-3-N	200002215

SPECIFICATIONS

Electrical	
Frequency	DC - 3 GHz
Max. Input Power	2 W
Impedance	50 Ω
Attenuation	See table below
VSWR	< 1.25:1

Mechanical	
Connection(s)	N male to N female
Dimensions	53 x 21 mm / 2.09 x 0.83"
Weight	0.071 kg / 0.16 lb

Environmental	
Operating Temperature Range	-35°C to +70°C

ADDITIONAL DATA

MODEL	ATTENUATION	ATT. DEVIATION	
		DC - 2.0 GHz	2.0 - 3.0 GHz
PRO-ATT 3 dB-2-3-N	3 dB	+/-0.2 dB	+/-0.3 dB
PRO-ATT 6 dB-2-3-N	6 dB	+/-0.2 dB	+/-0.3 dB
PRO-ATT 10 dB-2-3-N	10 dB	+/-0.2 dB	+/-0.3 dB
PRO-ATT 20 dB-2-3-N	20 dB	+/-0.2 dB	+/-0.3 dB
PRO-ATT 30 dB-2-3-N	30 dB	+/-0.5 dB	+/-1.5 dB

PROCOM A/S reserves the right to
amend specifications without prior notice