



Weatherproofing Kit for Connectors and Splices, includes butyl rubber and PVC tape

Product Classification

Product Type	Weatherproofing tape
Ordering Note	CommScope® standard product (Global)

General Specifications

Application	Provides additional moisture seal for cable connections
Applications per Kit	Four 1/2 in–7/8 in Twelve 1/2 in–1/2 in Twelve 1/2 in–7/8 in to device Two 1/2 in–2-1/4 in
Harmonized System (HS) Code	854420 (Coaxial cable and other coaxial electric conductors)

Dimensions

Nominal Size	1-1/4 in 1-5/8 in 1/2 in 1/4 in 2-1/4 in 3/8 in 5/8 in 7/8 in
--------------	---

Material Specifications

Material Type	Butyl rubber tape PVC tape
---------------	------------------------------

Environmental Specifications

UV Resistance Test Method	Butyl test method in QUV weatherometer cycle of 8 hours UV at 150 °F then 4 hours of condensation at 104 °F PVC tape test method UL 510, ASTM D1000
UV Resistance, minimum with no degradation	≥1000 hours
Weather Resistance Test Method	04AS00-03.6.0 MIL-STD-1344A, Method 1002

Packaging and Weights

Height, packed	7.7 in 195.58 mm
Width, packed	6.9 in 175.26 mm

221213

Length, packed	3.8 in 96.52 mm
Included	One roll of 2 in PVC tape Six rolls of 2-1/2 in butyl rubber tape Two rolls of 3/4 in PVC tape
Packaging quantity	1
Weight, gross	1.52 kg 3.351 lb

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant



Included Products

- 42615-10 — Butyl Rubber Tape, 24 in
- 9905-41 — Black 3/4 in PVC Tape, 66 ft
- 9905-71 — Black 2 in PVC Tape, 20 ft