# C2SGRIP



### Support Hoisting Grip for 3/8 in CNT-400 cable

Product Classification	
Product Type	Hoisting grip
Ordering Note	CommScope® non-standard product
General Specifications	
Attachment Spacing Intervals	60.96 m   200 ft
Hoisting Grip Type	Support hoisting grip
Installation Tool	Required, not included
Support Clamp	Included
Tool Туре	Hoisting grip
Dimensions	
Grip Length, minimum	101.6 mm   4 in
Leader Length, minimum	152.4 mm   6 in
Nominal Size	3/8 in
Electrical Specifications	
Return Loss Effect	0.1 dB
DTF Effect	0.1 dB
Material Specifications	
Material Type	Stainless steel   Tin-coated bronze
Mechanical Specifications	
Pull Load Capacity	158.757 kg   350 lb

Page 1 of 2

©2020 CommScope, Inc. All rights reserved. All trademarks identified by ® or <sup>™</sup> are registered trademarks, respectively, of CommScope. All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: August 29, 2020



## C2SGRIP

### Packaging and Weights

Height, packed	25.4 mm   1 in
Width, packed	177.8 mm   7 in
Length, packed	127 mm   5 in
Packaging quantity	1
Weight, gross	0.3 kg   0.661 lb

### Regulatory Compliance/Certifications

#### Classification

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant



©2020 CommScope, Inc. All rights reserved. All trademarks identified by ® or <sup>™</sup> are registered trademarks, respectively, of CommScope. All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: August 29, 2020

