

Coaxial Adapter N male - male, right angle

Coaxial Adapter N male - male, right angle



Technical Features

STRUCTURE

Product Line	Coaxial Cable Components
Product Type	Coaxial Adapter
Coaxial Cable Type	Foam Dielectric, Ultraflexible Foam Dielectric , Radiating Cable

MECHANICAL SPECIFICATIONS

Connector A	N Male
Center Contact Connector A	Brass, gold plated
Outer Contact Connector A	Brass, silver plated
Connector B	N Angle Male
Center Contact Connector B	Brass, gold plated
Outer Contact Connector B	Brass, silver plated
Body	copper alloy, nickel plated
Dielectric	PTFE
Gasket	Silicone rubber
Sealing class	IP68, connected

ELECTRICAL SPECIFICATIONS


Frequency Range	MHz	DC - 11000
VSWR, Return Loss	VSWR (dB)	0-500 MHz: 1.04 (34) 500 - 3700 MHz: 1.13 (24.3)
Insertion Loss (Max)	dB	0.02
3rd Order IM Product @ 2x20 Watts	dBc	< -165

TEMPERATURE SPECIFICATIONS

Operation Temperature	°C (°F)	-45 to 85 (-49 to 185)
-----------------------	---------	------------------------

PACKAGING INFORMATION

Package Quantity	1
------------------	---





Coaxial Adapter N male - male, right angle

External Document Links	Notes