

Coaxial Adapter N male - male

Coaxial Adapter N male - male



Technical Features

STRUCTURE

| | | |
|--------------------|--|--|
| Product Line | | Coaxial Cable Components |
| Product Type | | Coaxial Adapter |
| Coaxial Cable Type | | Foam Dielectric, Ultraflexible Foam Dielectric , Radiating Cable |

MECHANICAL SPECIFICATIONS

| | | |
|----------------------------|--|-----------------------------|
| Connector A | | N Male |
| Center Contact Connector A | | Brass, silver plated |
| Outer Contact Connector A | | Brass, silver plated |
| Connector B | | N Male |
| Center Contact Connector B | | Brass, silver plated |
| Outer Contact Connector B | | Brass, silver plated |
| Body | | copper alloy, nickel plated |
| Dielectric | | PTFE |
| Gasket | | Silicone rubber |
| Sealing class | | IP68, connected |

ELECTRICAL SPECIFICATIONS


| | | |
|-----------------------------------|-----------|---|
| Frequency Range | MHz | DC - 11000 |
| VSWR, Return Loss | VSWR (dB) | 0-1000 MHz: 1.02 (40) 1000-2000 MHz: 1.04 (34) 2000-3700 MHz: 1.10 (26.5) |
| Insertion Loss (Max) | dB | 0.02 |
| 3rd Order IM Product @ 2x20 Watts | dBc | < -165 |

TEMPERATURE SPECIFICATIONS

| | | |
|-----------------------|---------|------------------------|
| Operation Temperature | °C (°F) | -45 to 85 (-49 to 185) |
|-----------------------|---------|------------------------|

PACKAGING INFORMATION

| | | |
|------------------|--|---|
| Package Quantity | | 1 |
|------------------|--|---|





Coaxial Adapter N male - male

| External Document Links | Notes |
|-------------------------|-------|
| | |