SHK-78-2-P



Single Hanger Kit for 7/8 in coaxial cable, double stack; includes hardware and angle adapter

Product Classification

Product Type	Hanger kit
Product Brand	ValuSite™
Ordering Note	CommScope® standard product in Asia Pacific CommScope® standard product in Mexico, Central America, and South America

General Specifications

Cables per Hanger	2
Color	Black
Hanger Type	Composite clamp
Harmonized System (HS) Code	854420 (Coaxial cable and other coaxial electric conductors)
Mounting	M8 hardware
Dimensions	
Maximum Stack Height	2
Height	101.6 mm 4 in
Width	26.162 mm 1.03 in
Length	60.198 mm 2.37 in
Compatible Diameter, maximum	28.194 mm 1.11 in
Compatible Diameter, minimum	26.67 mm 1.05 in
Nominal Size	7/8 in
Electrical Specifications	
Return Loss Effect	0.1 dB
DTF Effect	0.1 dB

Page 1 of 2

©2022 CommScope, Inc. All rights reserved. All trademarks identified by ® or [™] are registered trademarks, respectively, of CommScope. All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: April 5, 2022

COMMSCOPE°

SHK-78-2-P

Material Specifications

Material Type	Engineered plastic Stainless steel
Mechanical Specifications	
Vibration Survival	≥4 hours at resonant frequency

Environmental Specifications

Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
Corrosion Resistance, minimum with no degredation	≥500 hours in salt spray chamber
Environmental Strength Capability	Double cable weight
UV Resistance, minimum with no degradation	\geq 100 hours exposure in accelerated UV life chamber

Packaging and Weights

Height, packed	15 cm 5.906 in
Width, packed	15 cm 5.906 in
Length, packed	3 cm 1.181 in
Included	Angle adapter Hardware
Packaging quantity	1
Weight, gross	0.45 kg 0.992 lb

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant

* Footnotes

Maximum Stack Height Fiber, Hybrid, Power

Page 2 of 2

