

Coaxial Adapter N male - female, right angle

Coaxial Adapter N male - female, right angle



Technical Features

STRUCTURE

| | |
|--------------------|--|
| Product Line | Coaxial Cable Components |
| Product Type | Coaxial Adapter |
| Coaxial Cable Type | Foam Dielectric, Ultraflexible Foam Dielectric , Radiating Cable |

MECHANICAL SPECIFICATIONS

| | |
|----------------------------|-----------------------------|
| Connector A | N Male |
| Center Contact Connector A | Spring Bronze, gold plated |
| Outer Contact Connector A | Brass, silver plated |
| Connector B | N Angle Female |
| Center Contact Connector B | Brass, silver plated |
| Outer Contact Connector B | Brass, silver plated |
| Body | copper alloy, nickel plated |
| Dielectric | PTFE |
| Gasket | Silicone rubber |
| Sealing class | IP68, connected |

ELECTRICAL SPECIFICATIONS


| | | |
|-----------------------------------|-----------|---|
| Frequency Range | MHz | DC - 8000 |
| VSWR, Return Loss | VSWR (dB) | 0-500 MHz: 1.04 (34) 500 - 3700 MHz: 1.13 (24.3) |
| Insertion Loss (Max) | dB | 0.02 |
| 3rd Order IM Product @ 2x20 Watts | dBc | < -165 |

TEMPERATURE SPECIFICATIONS

| | | |
|-----------------------|---------|------------------------|
| Operation Temperature | °C (°F) | -45 to 85 (-49 to 185) |
|-----------------------|---------|------------------------|

PACKAGING INFORMATION

| | |
|------------------|---|
| Package Quantity | 1 |
|------------------|---|





Coaxial Adapter N male - female, right angle

| External Document Links | Notes |
|-------------------------|-------|
| | |