



Connector for FLEXWELL® elliptical waveguide E185, PBR220 Flange

Standard connector for FLEXWELL® elliptical waveguide E185
with PBR220 flange, Plast 2000 sealed
frequency range: 17.7 - 19.7 GHz

FEATURES / BENEFITS

Superior Design

- ➞ Due to the precise manufacturing no tuning screws are necessary
- ➞ The terminations are brass passivated for good electrical performance
- ➞ A gas inlet is included



Quick & Easy Installation

- ➞ Different flaring tools are available
- ➞ No tuning in the field

Technical Features

STRUCTURE

Transmission Line Type		Elliptical Waveguide
Cable Type		E185
Model Series		E185 Series
Connector Frequency Range	GHz	17.7 - 19.7
Connector Type		Fixed
Sealing Method		Plast 2000
Plating Connector		Brass
Waterproof Level		IP68
Gas Inlet		G 1/8"
Connector Interface		PBR220

MECHANICAL SPECIFICATIONS

Length	mm (in)	90 (3.6)
Outer Diameter	mm (in)	40 (1.6)
Weight	kg (lb)	0.4 (0.88)
Sealing Volume	cm ³ (ounces)	20 (0.68)

External Document Links

Installation Instruction

Notes

Sealing component PLAST 2000 is **not** part of the connector delivery and must be ordered separately.