

Cold shrink Kit for 1/2 in through 7/8 in antenna and device 7/16 DIN connections

Product Classification

Product Type Cold shrink kit

Ordering Note CommScope® non-standard product

General Specifications

Application Provides additional moisture seal for cable connections

Applications per Kit One 1/2 in–7/8 in

Cable Family AL5-50 | AVA5-50 | FSJ4-50B | FSJ4-75A | LDF4-50A | LDF4-

75 | LDF5-50A | LDF5-75 | VXL5-50

Color Black

Dimensions

Length 7.99 in | 202.946 mm

Cable Diameter for Seal, maximum 21.34 mm | 0.84 in

Cable Diameter for Seal, minimum 16 mm | 0.63 in

Inner Diameter 53.09 mm | 2.09 in

Nominal Size 1/2 in | 7/8 in

Material Specifications

Material Type EPDM rubber

Environmental Specifications

UV Resistance Test MethodUV condensation reference ASTM-G-53, light source UVA 340 fluorescent lamp

UV Resistance, minimum with no degradation ≥1000 hours

Weather Resistance Test Method 04AS00-03.6.0 | MIL-STD-1344A, Method 1002

COMMSCOPE®

245174

Packaging and Weights

 Height, packed
 10 in | 254 mm

 Width, packed
 2.5 in | 63.5 mm

 Length, packed
 2.5 in | 63.5 mm

Included One EPDM rubber tube | One sealing foam strip

Packaging quantity 1

Weight, gross 0.16 kg | 0.353 lb

Regulatory Compliance/Certifications

Agency Classification

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

