

CA-TNRNF-V2



Type N Male to Type N Female Right Angle Adapter

Product Classification

Product Type	Adapter
Ordering Note	CommScope® standard product in Europe, the Middle East, and Africa

General Specifications


Body Style	Right angle
Inner Contact Plating	Silver
Interface	N Male
Interface 2	N Female
Mounting Angle	Right angle
Outer Contact Plating	Trimetal
Pressurizable	No

Dimensions

Width	32.38 mm 1.275 in
Length	36.59 mm 1.441 in
Diameter	20.25 mm 0.797 in

Outline Drawing

CA-TNRNF-V2



Electrical Specifications

Attenuation, Ambient Temperature	20 °C 68 °F
Average Power at Frequency	600.0 W @ 900 MHz
Connector Impedance	50 ohm
dc Test Voltage	2500 V
Inner Contact Resistance, maximum	1 mOhm
Insulation Resistance, minimum	5000 MOhm
Operating Frequency Band	0 – 8000 MHz
Outer Contact Resistance, maximum	0.25 mOhm
Peak Power, maximum	10 kW
RF Operating Voltage, maximum (vrms)	707 V

CA-TNRNF-V2

VSWR/Return Loss

Frequency Band	VSWR	Return Loss (dB)
0–3000 MHz	1.07	30
3000–6000 MHz	1.23	20

Mechanical Specifications

Coupling Nut Proof Torque	1.7 N-m 15.046 in lb
Coupling Nut Proof Torque Method	IEC 61169-16:9.3.6
Coupling Nut Retention Force	450 N 101.164 lbf
Coupling Nut Retention Force Method	IEC 61169-16:9.3.11
Insertion Force	28 N 6.295 lbf
Insertion Force Method	IEC 61169-16:9.3.5
Interface Durability	500 cycles
Interface Durability Method	IEC 61169-16:9.5
Mechanical Shock Test Method	IEC 60068-2-27

Environmental Specifications

Operating Temperature	-55 °C to +85 °C (-67 °F to +185 °F)
Storage Temperature	-65 °C to +125 °C (-85 °F to +257 °F)
Average Power, Ambient Temperature	40 °C 104 °F
Average Power, Inner Conductor Temperature	100 °C 212 °F
Climatic Sequence Test Method	IEC 60068-1
Corrosion Test Method	IEC 60068-2-11
Damp Heat Steady State Test Method	IEC 60068-2-3
Immersion Depth	1 m
Immersion Test Mating	Mated
Immersion Test Method	IEC 60529:2001, IP68
Thermal Shock Test Method	IEC 60068-2-14
Vibration Test Method	IEC 60068-2-6

Packaging and Weights

Weight, net	67.55 g 0.149 lb
--------------------	--------------------

CA-TNRNF-V2

Regulatory Compliance/Certifications

Agency

ISO 9001:2015

REACH-SVHC

ROHS



Classification

Designed, manufactured and/or distributed under this quality management system

Compliant as per SVHC revision on www.commscope.com/ProductCompliance

Compliant

* Footnotes

Immersion Depth

Immersion at specified depth for 24 hours