



## Connector for FLEXWELL® elliptical waveguide E60, PDR70 Flange

Standard connector for FLEXWELL® elliptical waveguide E60 with PDR70 flange, Plast 2000 sealed frequency range: 5.6 - 6.425 GHz

### FEATURES / BENEFITS

#### Superior Design

- ➡ Due to the precise manufacturing no tuning screws are necessary
- ➡ The terminations are brass passivated for good electrical performance
- ➡ A gas inlet is included



#### Quick & Easy Installation

- ➡ Different flaring tools are available
- ➡ No tuning in the field

### Technical Features

#### STRUCTURE

Transmission Line Type		Elliptical Waveguide
Cable Type		E60
Model Series		E60 Series
Connector Frequency Range	GHz	5.6 - 6.425
Connector Type		Fixed
Sealing Method		Plast 2000
Plating Connector		Brass
Waterproof Level		IP68
Gas Inlet		G 1/8"
Connector Interface		PDR70

#### MECHANICAL SPECIFICATIONS

Length	mm (in)	130 (5.1)
Outer Diameter	mm (in)	70 (2.8)
Weight	kg (lb)	2 (4.41)
Sealing Volume	cm <sup>3</sup> (ounces)	50 ( 1.69)

#### External Document Links

Installation Instruction

#### Notes

Sealing component PALST 2000 is **not** part of the connector delivery and must be ordered separately.