

DD113 TF2R Hand Microphone

Waterproof, dynamic hand microphone with three buttons

Article Number

01 6209 00100003 (former 2208-034-000-03)



Characteristics

- IP6K7 waterproof
- Dynamic microphone capsule
- Rugged chromed housing
- Durable spiral cable
- Protection against unintentional button presses
- Extremely durable switching contacts
- Interference field compensation

Scope of delivery

- Hand microphone with spiral cable
- Rubber protective ring for microphone head

Options

- Microphone preamplifier V966, V967, V856 and V857
- Customized plugs and cables
- Special button colours or symbols
- Black housing
- [Minor modifications and individual adaptations](#) on request

Application range

- Radio and PA systems for mobile and fixed applications in harsh environmental conditions

Accessories

- HV5 mount
- Rubber protective ring for microphone head

Specifications

General

Housing	Brass, silver
Dimensions	Length 177 mm, head Ø 33 mm, body Ø 24 mm
Weight	330 g (11.6 oz)
Connection	6-wire halogen-free spiral cable, 2 wires shielded, draw length 2.5 m max., without connector
Operating elements	3 buttons, green, orange, black
Storage temperature	-30 °C to +70 °C (-22 °F to +158 °F)
Operating temperature	-20 °C to +60 °C (-4 °F to +140 °F)
Certifications	DIN EN 50155:2018-05 DIN EN 45545-2:2016-02

Microphone

Frequency range	700 Hz to 4 kHz at -10 dB
Sensitivity	4 mV/Pa (-48 dBV/Pa ± 3 dB)
Impedance	200 Ohm ± 20 % at 1 kHz
Directivity	Omnidirectional