

DD112 TFR Hand Microphone

Dynamic hand microphone with two buttons

Article Number

01 6208 00500002 (former 2208-013-000-02)



Characteristics

- Dynamic microphone capsule
- Rugged chromed housing
- Durable spiral cable
- Very long life switching contact
- Interference field compensation

Scope of delivery

- Hand microphone with spiral cable

Options

- Splash protection for microphone capsule
- Protection against unintentional button presses
- Customized plugs and cables
- Special button colors or symbols
- Black housing
- [Minor modifications and individual adaptations](#) on request

Application range

- Radio and PA systems in mobile and fixed applications

Accessories

- HV5 mount
- Rubber protective ring for microphone head
- Microphone preamplifier V966, V967, V856 und V857

Specifications

General

Housing	Brass, silver
Dimensions	Length 173 mm, Head Ø 29 mm, Body Ø 24 mm
Weight	245 g (8.6 oz)
Connection	6-wire halogen free spiral cable, 2 Wires shielded, Draw length max. 1.5 m, without connector
Operating elements	2 Buttons, orange, black
Storage temperature	-30 °C to +70 °C (-22 °F to +158 °F)
Operation temperature	-20 °C to +60 °C (-4 °F to +140 °F)

Microphone

Frequency range	150 Hz to 4 kHz at -10 dB
Sensitivity	2 mV/Pa (-54 dBV/Pa ± 3 dB)
Impedance	200 Ohm ± 20 % at 1 kHz
Directivity	Omnidirectional