

DHL1/R (black) Loudspeaker

Compact horn loudspeaker

Article Number

01 6602 04500051



Characteristics

- Rugged flame-resistant plastic housing
- Very compact design
- High sound output
- Protection class IP65 (6K5) (IEC 60529; VW 80101)
- Salt fog resistant (IEC 60068; VW 80101)

Scope of delivery

- Horn loudspeaker with cable

Options

- Customized plugs
- 8 Ohm version
- [Minor modifications and individual adaptations](#) on request

Application range

- For mobile and fixed radio systems

Specifications

General

Housing	PA66 plastic, black, flame resistant acc. to UL94 V-0; NF F 16-101/102 I2/F2; BS6853 Table 7/8 Ib II
Dimensions	Depth 80 mm, height 125 mm, Ø 115 mm
Weight	940 g (33.1 oz)
Connection	2-wire cable, halogen free, 6 m, without connector
Storage temperature	-40 °C to +105 °C (-40 °F to +221 °F)
Operating temperature	-25 °C to +85 °C (-13 °F to +185 °F)

Loudspeaker

Frequency range	600 Hz to 4 kHz at -10 dB
Effective sound pressure	104 dB/1 W/1 m ± 3 dB
Impedance	4 Ohm ± 20 % at 1 kHz
Output	max. 25 W