

TM310 Gooseneck Microphone

Dynamic gooseneck microphone with On/Off switch

Article Number

01 6906 00200051



Characteristics

- Dynamic microphone capsule
- Unidirectional noise cancelling
- Rugged housing with gooseneck
- Long-life slide switch
- Interference field compensation

Scope of delivery

- Gooseneck microphone with cable

Options

- [Minor modifications and individual adaptations](#) on request

Application range

- Radio and PA system in mobile and fixed applications

Specifications

General

Housing	Brass, black
Gooseneck	Steel coil with external brass winding, black
Dimensions	Length 792 mm, head Ø 29 mm, body Ø 24 mm, gooseneck Ø 15 mm
Weight	726 g (25.6 oz)
Connection	4-wire cable, 2 wires shielded, 2.7 m, without connector
Storage temperature	-30 °C to +70 °C (-22 °F to +158 °F)
Operating temperature	-20 °C to +60 °C (-4 °F to +140 °F)
Operating elements	ON/OFF switch (slide switch), black

Microphone

Frequency range	300 Hz to 6 kHz at -10 dB
Sensitivity	1.5 mV/Pa (-56 dBV/Pa ± 3 dB)
Impedance	200 Ohm ± 20 % at 1 kHz
Directivity	Cardioid (at 1 kHz; 180° -15 dB)