

# TM880 SH Gooseneck Microphone

Dynamic gooseneck microphone with one button

## Article Number

01 6118 10100005



## Characteristics

- Dynamic microphone capsule
- Unidirectional high noise cancelling
- Rugged housing with gooseneck
- Extremely durable switching contact
- Protected against metal dust (INTERCEPT) and splash-proof

## Scope of delivery

- Gooseneck microphone with cable

## Options

- Customized plugs and cables
- Special button colours and symbols
- Various lengths of goosenecks
- Microphone preamplifier
- [Minor modifications and individual adaptations](#) on request

## Application range

- Radio and PA system in mobile applications

## Accessories

- Various mounting brackets for M14 screw thread

## Specifications

### General

Housing	Brass, black
Gooseneck	Steel coil with external brass winding, black
Dimensions	Length 650 mm, head Ø 29 mm, body Ø 24 mm, gooseneck Ø 18 mm
Weight	875 g (30.8 oz)
Connection	4-wire cable, 2 wires shielded, 4 m, without connector
Storage temperature	-25 °C to +70 °C (-13 °F to +158 °F)
Operating temperature	-20 °C to +60 °C (-4 °F to +140 °F)
Former Item Number	01 6118 00200005 2118-001-000-05

### Microphone

Frequency range	300 Hz to 8 kHz at -10 dB
Sensitivity	1.5 mV/Pa (-56 dBV/Pa ± 3 dB)
Impedance	200 Ohm ± 20 % at 1 kHz
Directivity	Cardioid (at 1 kHz; 180° -15 dB)