


Boxes

FTTA box small 6 RRH, 6 x LCD blau, 6x 4.8-7.0mm, SM

FTTA-C-00MM880006-000-00-202-O

Properties

- Ruggedized outdoor distribution box
- Protective vent to equalize pressure and prevent condensation
- Supports up to 6 remote radio heads



General data	
Number of remote radio heads (RRH)	6 pcs
Cabling System Compatibility	MASTERLINE Classic up to 12 fibers
Cable Input / Output	Input: 2x MLC 12 fibers (Ø 16mm)
	Output: 2x M25 Gland, 3-fold sealing (Ø 4.8-7.0mm) for up to 6 FO jumper
Installation temperature	-10 °C ... 50°C
Operation temperature	-40 °C ... 75°C
Ingress protection (IP Rating)	IP66
Free of halogene	Yes
UV resistance	Yes
Flammability rating	UL 94 V-0
Weight	1.5 kg
Dimensions (LxWxH)	255mm x 180mm x 65mm
Impact resistance	IK07
Protective vent typical airflow	2500 ml/min
Housing material	Glass-filled polycarbonate
Housing colour	Grey (RAL 7035)

Ordering Information Table	
Item number	Item description
85002620	FTTA-C-00SM880006-000-00-202-O

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/ EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P17640 / Date of publication: 31.10.2023 / uncontrolled copy