DATASHEET ANTENNA BASE

Smarteq[™] MidiMag[™] Magnetic Mount Antenna Base

Antenna Base – Colinear, Quarter Wave

1120.838, 1120.02.19.10+



Description

Magnetic mount antenna base for mobile and fixed applications.

Rod Compatibilty

- Colinear
- Quarter Wave

Features

- 27-1000MHz (depending on rod)
- Magnet mount
- M6 thread for rod





Smarteq[™] MidiMag[™] Magnetic Mount Antenna Base Antenna Base – Colinear, Quarter Wave

The Smarteq[™] MidiMag[™] is a magnet mount antenna base with a slim and steady design. The cable is easy to detach via FME connection any other cable is preferred. The connection is protected with shrinking tube. MidiMag[™] is a magnet mount antenna base with a slim and steady design. The cable is easy to detach via FME connection any other cable is preferred. The connection is protected with shrinking tube.

Features

- 27-500MHz (depending on rod)
- Magnetic mount
- M6 thread for rod

Certifications



Applications

- Critical Communications
- FirstNet
- Industrial IoT
- Intelligent Transportation

DATASHEET ID 550 023 I

PCTEL



Smarteq[™] MidiMag[™] Magnetic Mount Antenna Base

Antenna Base – Colinear, Quarter Wave

Standard Configurations

| Part Number | Thread for Rod | Cable Type | Cable Length | Connector | Installation | Color |
|----------------|-----------------------|------------|--------------|-----------|--------------|-------|
| 1120.02.19.10+ | M6 | RG58 | 4.5m | FME-f | Magnet | Black |
| 1120.838 | M6 | LL58 | 5m | TNC-m | Magnet | Black |

Electrical Specifications

| Frequency Ranges | 27-1000MHz | |
|-------------------|------------------|--|
| VSWR | Depending on rod | |
| Gain | Depending on rod | |
| Nominal Impedance | 50Ω | |
| Polarization | Vertical | |
| Max. Power | 50W | |

Mechanical and Environmental Specifications

| Dimensions (OD x H) | 59 x 54.5mm |
|---------------------------------|----------------------------|
| Weight | 400g |
| Materials Pin | Brass, black chromed |
| Isolator | PP, fiberglass reinforced |
| Base | Zinc, black powder lacquer |
| Sealing | Rubber |
| Magnet | Ferrite |
| Temperature (Storage/Operating) | -40°C to +85°C |
| Certifications | RoHS compliant |

For more information about this product contact your sales representative or visit > pctel.com/antenna-products

Solving Complex Wireless Challenges

PCTEL is a leading global provider of wireless technology solutions, including purpose-built Industrial IoT devices, antenna systems, and test and measurement products. Trusted by our customers for 29 years, we solve complex wireless challenges to help organizations stay connected, transform, and grow.



PCTEL, Inc. T: +1 630 372 6800 | pctel.com

Specifications subject to change without notice. PCTEL®, Smarteq™, and MidiMag™ are trademarks or registered trademarks of PCTEL, Inc. ©2023 PCTEL, Inc. All rights reserved. (November 2023)