### DATASHEET

## Smarteq<sup>™</sup> MiniWing<sup>™</sup> LTE **Multiband Antenna**

Cellular Antennas (5G, LTE, CBRS, 3G, 2G) -**Omnidirectional** 

710328, 710329, 710331, 710332, 710335



#### **Description**

Smarteq<sup>™</sup> MiniWing<sup>™</sup> is an omnidirectional multiband antenna with a slim and discreet design perfect for vehicles when outside installation is not an option.

#### **Technologies**

Cellular LTE 2G/3G/4G

#### **Features**

- Adhesive mounted
- Operating system: 2G/3G/4G
- Frequency: 790-960/1710-2690MHz
- Gain: 2dBi
- Color: Black







## Smarteq<sup>™</sup> MiniWing<sup>™</sup> LTE Multiband Antenna

Cellular Antennas (5G, LTE, CBRS, 3G, 2G) - Omnidirectional

The Smarteq<sup>™</sup> MiniWing<sup>™</sup> is an omnidirectional multiband antenna with a slim and discreet design. It is designed to meet a constant need for improved and reliable communication between vehicles and the cellular network. It is the perfect solution for vehicles when outside installation is not an option. MiniWing can also be used for different M2M applications.

#### **Features**

- Adhesive mounted
- Operating system: 2G/3G/4G
- Frequency: 790-960/1710-2690MHz
- Gain: 2dBi
- · Color: Black

#### **Applications**

- Intelligent Transportation Systems
- V2V
- M2M

#### **Certifications**







#### **SPECIFICATIONS**



## Smarteq<sup>™</sup> MiniWing<sup>™</sup> LTE Multiband Antenna

Cellular Antennas (5G, LTE, CBRS, 3G, 2G) - Omnidirectional

#### **Electrical Specifications**

Frequency Ranges	790-960MHz	1710-2170MHz	2400-2690MHz
VSWR (typical)	< 3.0:1	< 2.1:1	< 2.1:1
Peak Gain (typical)	2dBi	2dBi	2dBi
Total Efficiency (average)	40%	40%	40%
Number of Ports	1		
Impedance	50Ω		
Polarization	Linear		
Max power (ambient temp of 25°C)	10W		

#### **Mechanical and Environmental Specifications**

127 x 18 x 9.5mm		
16g (incl. 100mm cable and connector)		
RG174, black or Mini Low Loss Different cable lengths are available upon request		
SMA-m or FME-f Different connectors are available upon request		
Dryflex, FR4		
Black		
Adhesive mount on glass		
-40°C to +85°C		
IP44		
This part is RoHS compliant.		

#### **CONTACT US**

# For more information about this product contact your sales representative or visit

> pctel.com/antenna-products

#### **Solving Complex Wireless Challenges**

PCTEL is a leading global provider of wireless technology solutions, including purpose-built Industrial IoT devices, antenna systems, and test and measurement products. Trusted by our customers for 29 years, we solve complex wireless challenges to help organizations stay connected, transform, and grow.



PCTEL, Inc.

T: +1 630 372 6800 | pctel.com