

TM210 TF Hand Microphone

Dynamic hand microphone
with one button and 5-pol. binder connector

Article Number

01 6113 10100105



Characteristics

- Dynamische Dynamic microphone capsule
- Unidirectional noise cancelling
- Rugged chrome housing
- Durable spiral cable
- Extremely durable switching contacts

Scope of delivery

- Hand microphone with spiral cable and 5-pol. binder connector

Options

- Protection against unintentional button presses
- Customized plugs and cables
- Special button colours or symbols
- Black housing
- [Minor modifications and individual adaptations](#) on request

Application range

- Radio system in mobile and fixed applications

Accessories

- HV5 mount
- WS16 windscreen
- Microphone preamplifier V966, V967, V856 und V857

Specifications

General

Housing	Brass, black, powder-coated
Dimensions	Length 178 mm, Ø 24 mm
Weight	215 g (7.6 oz)
Connection	draw length 1.5 m max. and 5-pol. binder connector on the spiral cable
Operating and display elements	1 button, black
Storage temperature	-30 °C to +70 °C (-22 °F to +158 °F)
Operating temperature	-20 °C to +60 °C (-4 °F to +140 °F)
Former Item Number	01 6113 00100205

Microphone

Frequency range	150 Hz to 12 kHz at -10 dB
Sensitivity	1 mV/Pa (-60 dBV/Pa ± 3 dB)
Impedance	200 Ohm ± 20 % at 1 kHz
Directivity	Cardioid (at 1 kHz; 180° -20 dB)