# **Product Specifications**



## 15CIAMP-CNI-1B

KwikClamp<sup>™</sup> Hanger for 7/8 in coaxial cable, single stack; includes hardware



 KwikClamp<sup>™</sup> Series hangers are available only from select Andrew factories and warehouses in Europe

## **CHARACTERISTICS**

#### Dimensions

7/8 in
28.194 mm   1.110 in
26.670 mm   1.050 in
41.00 mm   1.61 in
46.00 mm   1.81 in
20.00 mm   0.79 in

#### **Electrical Specifications**

DTF Effect	0.1 dB
Return Loss Effect	0.1 dB

#### **General Specifications**

Hanger Type	KwikClamp™ hanger
Cables Per Hanger	1
Color	Black
Includes	Hardware
Material Type	Engineered plastic
Maximum Stack Height	1
Package Quantity	100

### **Mechanical Specifications**

Axial Load Capability, minimum with no cable slippage  $\geq 5$  times cable weight Corrosion Resistance minimum with no degredation ≥500 hours in salt spray chamber Channel section 40 x 22 x 1.5 mm Mounting

www.commscope.com/andrew

Join the Evolution

©2009 CommScope, Inc. All rights reserved.

All trademarks identified by ® or ™ are registered trademarks or trademarks, respectively, of CommScope. All specifications are subject to change. See www.commscope.com/andrew for the most current information.

# Product Specifications



L5CLAMP-CNL-1B

Operating Temperature UV Resistance, minimum with no degradation Vibration Survival

### Packed Dimensions

Height Length Shipping Weight Width -40 °C to +85 °C (-40 °F to +185 °F)  $\geq$ 100 hours exposure in accelerated UV life chamber  $\geq$ 4 hours at resonant frequency

36.0 cm | 14.2 in 22.0 cm | 8.7 in 10.00 kg | 22.05 lb 21.0 cm | 8.3 in

www.commscope.com/andrew

©2009 CommScope, Inc. All rights reserved. All trademarks identified by ® or ™ are registered trademarks or trademarks, respectively, of CommScope. All specifications are subject to change. See www.commscope.com/andrew for the most current information.



page 2 of 2 9/18/2009