

# F4CLAMP-CNLC-2B



KwikClamp™ Hanger for 1/2 in superflexible coaxial cable, double stack; includes hardware

- KwikClamp™ Series hangers are available only from select Andrew factories and warehouses in Europe

## Product Classification

<b>Brand</b>	KwikClamp™
<b>Product Type</b>	Hanger kit

## Dimensions

<b>Nominal Size</b>	1/2 in
<b>Compatible Diameter, maximum</b>	13.208 mm   0.520 in
<b>Compatible Diameter, minimum</b>	10.414 mm   0.410 in
<b>Height</b>	41.00 mm   1.61 in
<b>Length</b>	46.00 mm   1.81 in
<b>Width</b>	20.00 mm   0.79 in

## Electrical Specifications

<b>DTF Effect</b>	0.1 dB
<b>Return Loss Effect</b>	0.1 dB

## Environmental Specifications

<b>Operating Temperature</b>	-40 °C to +85 °C (-40 °F to +185 °F)
------------------------------	--------------------------------------

## General Specifications

<b>Hanger Type</b>	KwikClamp™ hanger
<b>Cables per Hanger</b>	1
<b>Color</b>	Black
<b>Includes</b>	Hardware
<b>Material Type</b>	Engineered plastic
<b>Maximum Stack Height</b>	2
<b>Ordering Note</b>	CommScope® standard product in Europe, the Middle East, and Africa
<b>Package Quantity</b>	100

# F4CLAMP-CNL-2B

---

## Mechanical Specifications

<b>Corrosion Resistance, minimum with no degradation</b>	≥500 hours in salt spray chamber
<b>Hanger Spacing, maximum</b>	0.9 m   3.0 ft
<b>Mounting</b>	Channel section 40 x 22 x 1.5 mm
<b>UV Resistance, minimum with no degradation</b>	≥100 hours exposure in accelerated UV life chamber
<b>Vibration Survival</b>	≥4 hours at resonant frequency
<b>Environmental Strength Capability</b>	Double cable weight

## Packed Dimensions

<b>Height</b>	30.0 cm   11.8 in
<b>Length</b>	26.0 cm   10.2 in
<b>Shipping Weight</b>	10.00 kg   22.05 lb
<b>Width</b>	27.0 cm   10.6 in

## \* Footnotes

**Maximum Stack Height** Fiber, Hybrid, Power