

F4CLAMP-CN1-1B



KwikClamp™ Hanger for 1/2 in superflexible coaxial cable, single stack; includes hardware

- KwikClamp™ Series hangers are available only from select Andrew factories and warehouses in Europe

Product Classification

Brand	KwikClamp™
Product Type	Hanger kit

Dimensions

Nominal Size	1/2 in
Compatible Diameter, maximum	13.208 mm 0.520 in
Compatible Diameter, minimum	10.414 mm 0.410 in
Height	41.00 mm 1.61 in
Length	46.00 mm 1.81 in
Width	20.00 mm 0.79 in

Electrical Specifications

DTF Effect	0.1 dB
Return Loss Effect	0.1 dB

Environmental Specifications

Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
------------------------------	--------------------------------------

General Specifications

Hanger Type	KwikClamp™ hanger
Cables per Hanger	1
Color	Black
Includes	Hardware
Material Type	Engineered plastic
Maximum Stack Height	1
Ordering Note	CommScope® non-standard product
Package Quantity	100

F4CLAMP-CN1-1B

Mechanical Specifications

Corrosion Resistance, minimum with no degradation	≥500 hours in salt spray chamber
Hanger Spacing, maximum	0.9 m 3.0 ft
Mounting	Channel section 40 x 22 x 1.5 mm
UV Resistance, minimum with no degradation	≥100 hours exposure in accelerated UV life chamber
Vibration Survival	≥4 hours at resonant frequency
Environmental Strength Capability	Double cable weight

Packed Dimensions

Height	30.0 cm 11.8 in
Length	22.0 cm 8.7 in
Shipping Weight	7.00 kg 15.43 lb
Width	27.0 cm 10.6 in

* Footnotes

Maximum Stack Height Fiber, Hybrid, Power