



## FLEXWELL® Standard Elliptical Waveguide

FLEXWELL® elliptical waveguide is constructed of longitudinally continuous seam welded, highly conductive copper tube, corrugated and precision formed into an elliptical cross section. It is manufactured in continuous lengths using a special seam welding process developed by the RFS organization.

The corrugation design achieves high transverse stability, flexibility and crush strength for superior handling and forming at an installation. The inherent strength and flexibility of FLEXWELL® waveguide allows on location, a continuous length of waveguide to be run directly from a tower-mounted antenna to the equipment building.

A FLEXWELL® elliptical waveguide feeder requires less planning and reduces installation costs when compared to a feeder system using a rigid rectangular waveguide. FLEXWELL® waveguide is available cut to length with factory attached connectors or in continuous lengths for termination in the field.



### FEATURES / BENEFITS

- ➔ Designed for optimum system performance
- ➔ Excellent electrical performance
- ➔ Low loss and low VSWR (low return loss)
- ➔ Electrical test made on every waveguide during manufacturing
- ➔ Every waveguide undergoes 24 hour pressure test
- ➔ Reduced installation cost compared to rigid rectangular waveguides due to flexibility
- ➔ No need of flange joints, twist section and bends
- ➔ Easy transportation in coils or on drums
- ➔ Cutting at exact length and connectorizing in the field

### Technical Features

#### GENERAL SPECIFICATIONS

<b>Performance</b>		Standard
<b>Jacket</b>		J (Polyethylene black)

#### ELECTRICAL SPECIFICATIONS

<b>Typical Operating Band</b>	GHz	5.9 - 7.125
<b>Max. VSWR / Return Loss</b>	dB	1.15 / 23.1
<b>Cut-off Frequency</b>	GHz	4.01

#### MECHANICAL SPECIFICATIONS

<b>Dimension over Jacket</b>	mm (in)	51 x 30 (2.0 x 1.2)
<b>Weight</b>	kg/m (lb/ft)	0.75 (0.5)
<b>Minimum Bending Radius E Plane, Single Bend</b>	mm (in)	200 (8)
<b>Minimum Bending Radius H Plane, Single Bend</b>	mm (in)	500 (20)
<b>Minimum Bending Radius E Plane, Repeated Bends</b>	mm (in)	300 (12)
<b>Minimum Bending Radius H Plane, Repeated Bends</b>	mm (in)	600 (24)
<b>Maximum Twist</b>	degree/m (degree/ft)	5 (1.5)
<b>Max. Operating Pressure</b>	bar (psi)	0.5 (7)
<b>Max. Pulling Length per Hoisting Grip</b>	m (ft)	100 (305)
<b>Standard Hanger Spacing</b>	m (ft)	0.9 (3)

#### TEMPERATURE SPECIFICATIONS

<b>Installation Temperature</b>	°C (°F)	-40 to 60 (-40 to 140 )
<b>Storage Temperature</b>	°C (°F)	-70 to 85 (-94 to 185 )
<b>Operation Temperature</b>	°C (°F)	-50 to 85 (-58 to 185 )



## FLEXWELL® Standard Elliptical Waveguide

### ATTENUATION AND POWER RATING

Frequency GHz	Attenuation		Avg. Power kW	Group Vel. %c	Group Delay	
	dB/100m	dB/100ft			ns/100m	ns/100ft
5.9	4.92	1.50	4.82	73.4	454.7	138.6
6.0	4.84	1.47	4.90	74.4	448.4	136.7
6.1	4.76	1.45	4.98	75.4	442.6	134.9
6.2	4.69	1.43	5.06	76.3	437.4	133.3
6.3	4.62	1.41	5.13	77.1	432.5	131.8
6.4	4.56	1.39	5.19	77.9	428.0	130.5
6.5	4.51	1.37	5.26	78.7	423.8	129.2
6.6	4.46	1.36	5.32	79.4	420.0	128.0
6.7	4.41	1.34	5.37	80.1	416.4	126.9
6.8	4.37	1.33	5.42	80.8	413.0	125.9
6.9	4.33	1.32	5.47	81.4	409.9	124.9
7.0	4.29	1.31	5.52	82.0	407.0	124.0
7.125	4.25	1.30	5.58	82.7	403.5	123.0

For attenuation: VSWR 1.0, ambient temperature 28°C (68°F)  
 For average power: VSWR 1.0 and 42°C (76°F) temperature rise 40°C (104°F)

### External Document Links

### Notes

VSWR values include connectors and are valid for frequency band of connectors.  
 Max. Operating Band: 5.00 - 7.125 GHz